





NET-TROL®

WOOD CLEANER & COLOUR RESTORER

Product description	NET-TROL [®] is a powerful cleaner and brightener which restores grey, weather-beaten exterior wood that is unfinished to its natural colour. Unlike bleach or chlorine based cleaners it will not damage the wood fibres. NET-TROL [®] removes surface and ground in dirt while restoring a bright, vibrant look to the exterior surface.
Properties	 Lightens and restores colour to all greyed weathered wood without bleaching. Fast acting, restores greyed weathered wood to its natural colour within 15 minutes. Use on all wood species: Softwood (inc pressure treated wood) - Larch, Pine, Cedar; Ultra Heat Treated Wood; Hardwoods - Teak, Iroko, Ipe, Bangkirai (Balau), Oak, Chestnut Cleans and neutralises staining caused by tannins. Excellent degreaser for tropical hardwoods prior to applying the chosen finish. Removes all traces of weathering attributed to mould, mildew, pollution Restores luster to plastics dulled by weathering and UV rays. Removes rust stains. Cleans discoloured stone and stained cement. Neutralises surfaces stripped with DILUNETT®*, AQUANETT®*, PREPDECK®* or CDKP® 90*. Safe to use - harmless to plants and shrubs. Biodegradable - Does not contain solvents or bleach - rinse with water.
Basic uses	 Exterior use only. Removal of weathered grey wood fibres from untreated timber. Horizontal or Vertical surfaces - cladding, fences, decks (boat & garden), garden furniture Previously coated exterior wood surfaces in need of cleaning. Other surfaces: rust stained cement, discoloured stone, plastic, GRP.
Technical data	 Solvent type: Water. Specific gravity (at 20°C): 1,07 ± 0,05. Physical state: Gel. Solid content: 19% ± 2. Flash point: Not classified as flammable. Shelf life: 18 months minimum in original unopened packaging. Container size: 1L, 2.5L, 15L. Appearance and odour: Blue, fresh soap odour. VOC: Out of scope.
Application tools	Soft brush. Stiff bristle/nylon brush. Powerwasher. Wear chemical resistant gloves, safety goggles and protective clothing.
Good application practice	Shake container thoroughly before use. Cover areas you want to protect. Thoroughly wet plants and shrubs. Apply between 5°C and 35°C. Do not apply on a hot surface; product will dry too quickly. If cleaning vertical wood, work from bottom to top to avoid streaking.

n 0
NSI
npe
nis si
under
ge
made
not
g
odu
b b
0 L
atio
apl
the
e,
utactur
tao
Janu
Ĕ
the
đ
Ę
ISUC
esp
ě
not the
are
B
B
ive a
патие а
lustrative a
y illustrative and are
urely illustrative a
e purely i
e purely i
cons are purely 1
prmation set out cons are purely i
information set out cons are purely i
prmation set out cons are purely

Application	 CAUTION: Surfaces may be slippery when wet. Use caution when walking on wet surfaces during application. NET-TROL® may dull painted surfaces and some metal fixings if left on to long. Rinse off quickly or wipe with a wet cloth. Wood. stone. concrete: Wet surface with fresh, clean water. Apply NET-TROL® with a synthetic brush or roller (medium or long pile). Scrub surface with a stiff nylon/synthetic brush. Leave to stand for approx 10-20 minutes. If surface starts to dry, dampen with a mist application of water. Scrub surface whilst rinsing with water or use a pressure washer (max. 60 bar). If required repeat procedure. Wood - Allow to dry 48 hours or until it meets the moisture content required by the chosen finish. Stone & Concrete - Allow to dry until it meets the moisture content required by the chosen finish. Stone & Concrete - Allow to dry until it meets the moisture content required by the chosen finish/ sealer. Nail stains: Clean surface. After cleaning wet surface with fresh clean water. Apply NET-TROL® to the entire surface over and around the nail stain. Do not rinse until the stain has disappeared. Plastic or GRP: Wet surface with a soft or medium nylon scrubbing brush. Leave to work for 10 minutes. Scrub surface with a soft or medium nylon scrubbing brush. Rinse with large amounts of fresh clean water. Apply NET-TROL® with a stiff nylon scrubbing brush working in to rust stain. Leave to work for 10 minutes. Scrub surface with stiff nylon scrubbing brush. 	The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.
Coverage	Rinse with large amounts of fresh clean water. 5 to 10 m ² per litre. Actual coverage will vary depending on type, age and texture of surface.	
Restrictions	Do not use an aluminium.	
Clean-up	Soap and water.	
After cleaning	Protect and enhance the natural beauty of exterior wood with the chosen OWATROL® finish.	
Storage	Store unused portion in tightly closed plastic or glass container. Do not store in metal containers. Keep from freezing and high temperatures.	
General Information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local OWATROL Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.	
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.	484
Issue date	May 2012.	rs 331 998
	* Same manufacturer	07/12 - RCS Tours 331 998 484
	NET-TROL® is a trademark	U

Jurieu

OWATROL INTERNATIONAL SLU Barcelona - Spain

