



INTERIOR
EXTERIOR



GELCOAT RESTORER

COLOR RESTORER

<h3>Product description</h3>	<p>GELCOAT RESTORER is a deep penetrating oil that penetrates deep into gelcoat to re-wet the pigment and so restore the dull, faded look of the gelcoat to its original color and lustre; it then dries to a tough, long lasting and flexible finish. GELCOAT RESTORER eliminates the need for expensive waxes and polishes that sit on the surface and dry out quickly.</p>
<h3>Properties</h3>	<ul style="list-style-type: none"> • Restores original color and dries to a tough flexible finish. • Long lasting and penetrates deep into gelcoat. • Eliminates the need for waxes and polishes that sit on surfaces and dry out quickly. • Easy to apply - easy to maintain.
<h3>Basic uses</h3>	<ul style="list-style-type: none"> • Works on gelcoat, plastic, paint, stone. • Horizontal or Vertical surfaces.
<h3>Technical data</h3>	<p>Vehicle Type: Alkyd resins.</p> <p>Solvent Type: Solvent.</p> <p>Viscosity: Fluid.</p> <p>Specific Gravity: 0,857 ± 0,05 (68°F - 20°C).</p> <p>Physical State: Liquid.</p> <p>Solid Content: 33% ± 2.</p> <p>Flammability: Not classified as flammable.</p> <p>Flash Point: > 140°F (60°C).</p> <p>Shelf Life: 2 years minimum in original unopened packaging.</p> <p>Container Size: 0.5L (0.53 U.S. QUART), 1L (1.06 U.S. QUART).</p> <p>Color: Amber.</p> <p>Dry Time: 24 hours, depending on temperature and humidity.</p> <p>VOC: Does not exceed 580 g/l (4.84 lb/gal).</p>
<h3>Application tools</h3>	<ul style="list-style-type: none"> • Brush: High quality, natural or synthetic bristle brush. • SOFT cloth.
<h3>Good application practice</h3>	<ul style="list-style-type: none"> • Choose an area that can be managed within five minutes. Excess GELCOAT RESTORER that dries on the surface may be removed with MARINE STRIP* per label instructions. • Wear protective clothing and gloves. • Cover areas you want to protect. • Apply between 41°F (5°C) and 95°F (35°C). • Do not apply in direct sunlight. • Use as is, do not thin.

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

Application	<ul style="list-style-type: none"> • Rinse the surface with fresh water. Remove dirt and heavy oxidation by scrubbing with DECK CLEANER* per label instructions. Allow surface to completely dry. • Saturate a SOFT cloth with GELCOAT RESTORER and wipe it on. • With a SOFT cloth, wipe off excess within 10 minutes. • Gently polish with a lint-free cloth to a new sheen.
Coverage	<ul style="list-style-type: none"> • 193 ft² (18 m²) per litre. • Actual coverage will vary depending on type, age and texture of surface.
Clean-up	<p>Clean all tools and equipment with mineral spirits while still wet. If allowed to dry, remove with paint stripper.</p> <p>NOTE: Any rags, steel wool etc soaked in GELCOAT RESTORER may spontaneously catch fire if improperly discarded. Rags, steel wool etc must be saturated with water after use or placed in a sealed, water filled metal container, before disposing with household waste.</p>
Storage	<ul style="list-style-type: none"> • Left over GELCOAT RESTORER should be transferred to a smaller, airtight, closed metal or glass container. • Keep from freezing and high temperature.
General information	<p>Every care is taken to ensure that the information provided in this technical data sheet is accurate. OWATROL COATINGS USA is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advise and information please contact our technical department on (954)-929-3905 or email info@deksolje.com.</p> <p>The information above is correct at the date of issue.</p>
Safety	<p>Keep out of the reach of children.</p> <p>MSDS available at www.deksolje.com.</p>
Issue date	November 2011.

* Same manufacturer

