

OWATAUD

AWNING AND COVER CLEANER

Description	Fast acting and easy to use, OWATAUD cleans the surface without damaging or altering it, removing dirt, marks and stains due to grease, pollution, exhaust fumes from awnings and covers as well as artificial leather, vinyl, glass, biminis
Properties	 Quickly and thoroughly removes dirt, marks and stains caused by air pollution, exhaust fumes, bad weather, residue from quay and wharf oils Cleans exhaust fumes, black marks and grease from dirty and stained sails Degreases and restores the treated surface to its original condition. Fast acting and easy to use. Does not damage or alter the cleaned surface.
Basic uses	 Exterior. Seating and cushions made of vinyl and artificial leather. Sails, Covers, Dodgers, Biminis, Glass (translucent parts) of PVC. Fabric surfaces (test on a small area first).
Technical data	Composition: Surfactants and high performance emulsifiers. Solvent type: Water Specific Gravity at 20°C (68°F): 1.0 ± 0.1 Viscosity: Liquid/Fluid PH: 9 ± 1 Flash point: Not classified as flammable. Container size: 1L Colour: Light yellow Shelf life: 1 year in original unopened packaging. VOC: N/A under EU Directive 2004/42
Application tools	Brush. Cloth. Scrubbing Sponge. Sprayer.
Good application practice	Do not apply in direct sunlight or to hot surfaces. Apply between 10°C (50°F) and 30°C (86°F). Do not use wire brushes to scrub the surface. Protect surfaces you do not wish to treat. Always test on a small inconspicuous area first. Use appropriate protective clothing – Gloves, Goggles
Dilutions	Use as is. Do not dilute.
Application	Apply OWATAUD to the surface using a brush or sprayer. Allow to work for 5 minutes. Rub surface with a clean cloth or scrubbing sponge. Rinse with fresh clean water. Repeat process if required. TIP: For very dirty surfaces soak cloth or scrubbing sponge in OWATAUD and scrub on to surface in a circular motion. If surface is too hot, dampen with water to cool before applying OWATAUD.
Clean-up	Water Note: Cloths soaked in OWATAUD should be laid out flat to dry before disposing.
Storage	Store left over product in original container. Close lid tightly after use. Keep from freezing and high temperatures.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	January 2017

* Same manufacturer

Owatrol Marine is a trademark



Find all our solutions: www.owatrol.com