



SPIRIT SEALER NEUTRALISER

Description	SPIRIT SEALER neutralises the effect of RUST SPIRIT*, COPPER SPIRIT* AND BRONZE SPIRIT*. Stopping the oxidising effect of these three products, SPIRIT SEALER allows you to fix the decorative effect and colour once the desired level of oxidising has been achieved.
Properties	Odourless. Waterbased. Neutraliser – Prevents further oxidisation of the treated surface.
Basic uses	Easy application. Locks in the decorative effect of RUST SPIRIT*, COPPER SPIRIT* and BRONZE SPIRIT*.
Technical data	Finish: Satin. Vehicle Type: Specific Resins. Solvent Type: Water. Specific Gravity at 20°C (68°F): 1.05 ± 0.03. Solid Content: 38 ± 3%. Drying Time at 20°C (68°F) and 50% RH: 6 hours (Minimum). Container Size: 500ml, 2.5Ltr. Colour: Clear. Appearance in can: White. Shelf Life: 1 year in original, unopened packaging. VOC: EU limit value for this product (cat A /i): 140 g/l (2010). This product contains max 50 g/l.
Good application practice	Cover and protect everything you do not wish to coat. Apply between 5°C and 25°C. Do not apply to hot surfaces.
Application tools	Brush. Roller.
Surface preparation	Surfaces must have previously been treated with RUST SPIRIT*, COPPER SPIRIT* or BRONZE SPIRIT*.
Application	Use as is. Do not thin. Stir well before use. Avoiding over application, apply an even coat of SPIRIT SEALER to the entire decorated area, to neutralise and stop the oxidising process of RUST SPIRIT*, COPPER SPIRIT* OR BRONZE SPIRIT*. Allow to dry. Note: For maximum protection apply NATURAL VARNISH* or OWATROL OIL* depending on the desired final finish. SPIRIT SEALER is not required where OWATROL OIL* is applied as the final finish.
Coverage	8-12m² per litre. Coverage will depend on application method, type, texture, age, and porosity of the surface.

Clean-up	Soap and water.
Storage	Keep from freezing and high temperatures. Store in original container and close lid tightly after use.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the Technical Data Sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	November 2017

* Same manufacture

Owatrol Spirit is a trademark

