



ABSOLUTE PRIMER

SMOOTH SURFACE PRIMER

Description	ABSOLUTE PRIMER is a primer coat for bonding products from the SPIRIT range to smooth, difficult and non-porous surfaces.
Properties	<ul style="list-style-type: none"> • Excellent adhesion. • Primer for the OWATROL SPIRIT product range. • Odourless. • Waterbased.
Basic Uses	<ul style="list-style-type: none"> • Interior and exterior. • All non-porous and difficult to adhere to surfaces. <ul style="list-style-type: none"> - Non-ferrous and Galvanised metals, Stainless Steel. - Plastics (see Restrictions). <div data-bbox="488 898 796 1207" data-label="Image"> </div> <p>- Glass, Ceramics....</p> <p><i>Example of application on glass</i></p>
Technical data	<p>Appearance: Chalky Sublayer.</p> <p>Vehicle Type: High-adhesion Resins.</p> <p>Solvent Type: Water.</p> <p>Specific Gravity at 20°C (68°F): 1.30 ± 0.03.</p> <p>Solid Content: 56 ± 3%.</p> <p>Drying Time at 20°C (68°F) and 50% RH: 8 hours.</p> <p>Container Size: 500ml, 2.5Ltr.</p> <p>Shelf Life: 1 year in original, unopened packaging.</p> <p>VOC: EU limit for this product (cat A /i): 140 g/l VOC (2010). This product contains a maximum of 15g/l.</p>
Good application practice	<p>Cover and protect everything you do not wish to coat.</p> <p>Apply between 5°C and 25°C.</p> <p>Do not apply to hot surfaces.</p>
Application tools	<p>Brush.</p> <p>Roller.</p>
Surface preparation	<p>Surfaces must be in good sound condition, clean, dry and free of all grease, oil and other surface contamination.</p> <p>Meticulously clean surface using a suitable cleaning agent depending on the substrate and contamination e.g. Acetone, Hot Soapy Water (rinse thoroughly) etc.</p> <p>Allow to dry.</p> <p>Sand plastic and shiny surface with fine grit abrasive to improve adhesion.</p> <p>Thoroughly dust off.</p>

Application	Use as is. Do not thin. Shake or stir well before use. Apply an even application of ABSOLUTE PRIMER. Allow to dry. Finish with a product from the OWATROL® SPIRIT range.
Restrictions	Do not use on Polyethylene or Polypropylene plastics.
Coverage	8-10m ² per litre. Coverage will depend on application method, type, texture, age and porosity of the surface.
Clean-up	Soap and water.
Storage	Keep from freezing and high temperatures. Store in original container and close lid tightly after use.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the Technical Data Sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	November 2017

* Same manufacture

The information presented here is given for information purposes only and does not engage the liability of the manufacturer, as the application of products is not carried out under its control. * Information on the level of omissions of volatile substances in indoor air, presenting a risk of toxicity through inhalation, on a classification scale ranging from A+ (variable omissions) to C (high omissions).

**Owatrol Spirit
is a trademark**



OWATROL INTERNATIONAL SLU
Barcelona – Spain
Tel. +34 93 125 88 68
Fax +34 93 106 02 13

Find all our solutions:
www.owatrol.com