



# AUSSIE-TROL®

CELL ACTIVATOR FOR ACRYLIC  
POURING



## PRODUCT DESCRIPTION

AUSSIE-TROL® is a water-based additive that alters the sliding and tensile properties of acrylic paints used in pouring techniques as a supplement to FLOETROL®. It makes it possible to multiply and vary shapes and motifs.

## BASIC USES

- Water-based additive for acrylic paint
- Canvas, Table Top, Furniture....

## PROPERTIES

- Improves the spread of the paint on the canvas.
- Improves the colour gradient.
- Preserves the brightness, opacity and texture of the colours.
- Excellent separation of colours.
- Optimises the formation of cells and lacing.
- Works with premixed pouring products.

<b>FINISH</b> N/A	<b>SIZES</b> 500ml	<b>USAGE</b> Interior
----------------------	-----------------------	--------------------------

## TECHNICAL DATA

<b>Vehicle Type</b>	Siloxane polymer and Vinyl copolymer
<b>Solvent Type</b>	Water
<b>Odour</b>	Odourless
<b>pH</b>	8-9
<b>Specific Gravity</b>	At 20°C (68°F) 1.00 +/-0.05
<b>Viscosity</b>	Fluid
<b>Solid Content</b>	12.5% +/-2%
<b>Appearance</b>	Translucent white
<b>Flash point</b>	Not classified as flammable
<b>Shelf Life</b>	1 year minimum in original unopened packaging
<b>VOC</b>	Outside the scope of EC Directive 2004-42
<b>Application Tools</b>	Use the usual equipment for pouring techniques
<b>Dilution</b>	Use as is. Do not dilute
<b>Mixing Ratios</b>	2 parts AUSSIE-TROL® to 1 part paint up to a MAXIMUM of 5 parts AUSSIE-TROL® to 1 part paint
<b>Drying Times</b>	As per paint manufacturers guidelines. <b>However</b> depending on the type of acrylic paint used and the chosen mixing ratios, the paints may take a lot longer to dry and their surface hardness may be altered. This may cause fragility upon handling and leave marks when the paint is touched. This phenomenon may be mitigated through the use of a varnish. Furthermore, a varnish will help to produce a uniform shine. <b>Warning:</b> If you finish your painting with a varnish and this varnish is too rigid or brittle, there may be a risk of cracking. <b>To ensure that the paint is completely dry, we recommend a long drying period (at least 1 week) before applying a varnish.</b>
<b>Clean-up</b>	Water
<b>Storage</b>	Close lid tightly after use and store in original container Keep from freezing and high temperatures

## GOOD APPLICATION PRACTICE

Cover and protect everything you do not wish to paint.  
Moisture content of wood should be 18% or less.  
Apply between 10°C (50°F) and 30°C (86°F).  
Do not apply to hot surfaces.

## SURFACE PREPARATION

Prepare surface as per the instructions on the paint can.  
Remove all loose and flaking material.  
Ensure surface is clean, dry and free from grease grime and any other surface contamination.

## PRODUCT PREPARATION

Shake AUSSIE-TROL® well before use.  
Work step by step. Effects may vary depending on the paint which AUSSIE-TROL® is added to. We recommend that you initially add a small amount of AUSSIE-TROL® (2 parts to 1 part paint), do a test and adjust the quantity if required to obtain the desired mix and consistency.  
Depending on the desired effects and fluidity, it is possible to increase the proportion of AUSSIE-TROL® up to 5 parts to 1 part paint. Mix again thoroughly.  
Do not dilute the mixture.  
If AUSSIE-TROL® is used simultaneously in several different paints, it is best not to use the same proportion of AUSSIE-TROL®.  
When AUSSIE-TROL® is added in a high ratio, it can affect the surface shine of the different acrylic paints, which it is added to.  
The types of colouring and wetting agents used in the coloured paints can affect the performance of AUSSIE-TROL®. Effects may thus vary from one colour to another. The proportion of AUSSIE-TROL® can be adjusted according to the colour of the paint.

## APPLICATION

On the medium to be decorated, first pour on the base or "pillow" paint.  
This paint must be fluid but not too runny. It will serve as a vector for the sliding of the colours. We recommend a standard white acrylic paint.  
This paint must NOT be mixed with FLOETROL®\*.  
On the pillow, pour on the coloured paints, which maybe mixed with FLOETROL® if desired. They can all be poured in the same place or in various places but all on the white pillow.  
In order to optimise the effects, vary the shapes and sizes of the cells, and further increase the interactions of the colours, pour, as a last step, the paint mixed with AUSSIE-TROL®. When poured on top of each of the areas where the paints have been applied, AUSSIE-TROL® will improve the spread of the cells and provide more latitude to create new shapes.  
For the mix with AUSSIE-TROL®, we advise you to use paint of the same colour as the "pillow".  
Blow intermittently through a straw or with your mouth on the colour "islets" from the centre outwards.  
The colours slide and move apart. Cells appear.  
Let your creativity and imagination do the rest. Continue blowing using a rotating or swinging movement to move the paints and the "pillow" as you like to finish your work.





## APPLICATION & TRANSFORMATION TECHNIQUES

Feather, Small Chain, String....

This method consists of soaking the item into the paint mixed with the pouring medium. The item is then placed onto the piece covered with the "pillow" or onto a freshly flowed or blown pouring and moved around it.

Comb.

This method consists in sliding a comb on a paint flow to spread the colours and/or create cells.

## RESTRICTIONS

Do not use AUSSIE –TROL® with oil or alkyd based paints.

## SAFETY

Refer to the safety data sheet (MSDS) available at [www.owatrol.com](http://www.owatrol.com) and text on the packaging. Keep out of the reach of children

---

This Technical Data sheet cancels and replaces any previous Technical Data sheet for the same product. Its purpose is to inform the user about the product. The information contained within this Technical Data sheet is based on our current knowledge. However, the information contained within this document cannot replace a specification appropriate to the nature and conditions of the substrate to be coated. Due to ongoing technical advances, it is the responsibility of the user to establish that this document has not been superseded by a more recent edition. The information contained within this document is for guidance only and the manufacturer is unable to guarantee or accept responsibility for the results as it has no control over the conditions under which its products are applied.

**Publication Date 07/10/2022**

---

DURIEU S.A. - 91070 Bondoufle - France

Tel. +33 (0)1 60 86 48 70

Fax +33 (0)1 60 86 84 84

OWATROL INTERNATIONAL S.L.U.

08006 Barcelona – Spain

Tel. +34 93 125 88 68

Owatrol®  
is a trademark



Find all our solutions at  
[www.owatrol.com](http://www.owatrol.com)

Our technical department is at your disposal to  
answer any questions you may have at  
[info@owatrol.com](mailto:info@owatrol.com)